## NSN 4720-01-168-1929



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-01-168-1929 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.250 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 160.0 degrees fahrenheit single response **Outside Diameter:** 0.469 inches **Minimum Inside Bending Radius:** 4.000 inches **Connection Style:** Swivel nut flare 2nd end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Features Provided:** Internal support and reusable end fittings **Burst Test Pressure:** 1250.0 pounds per square inch **Layer Composition And Location:** 1st layer braided cotton cord and outer layer molded rubber, synthetic **Maximum Operating Pressure:** 200.0 pounds per square inch **Thread Size:** 0.438 inches 1st end Seat Angle: 37.0 degrees 2nd end Flow Angle: 45.0 degrees 2nd end **Inside Surface Condition:** Smooth **Measuring Method And Length:** 

22.000 inches working Media For Which Designed: Air single response **Thread Series Designator:** Unjf 1st end

## NSN 4720-01-168-1929

Nonmetallic Hose Assembly - Page 2 of 2



Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A542a0