NSN 4720-01-168-7529

Nonmetallic Hose Assembly - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/4720-01-168-7529 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.437 inches **Tempurature Rating:** -65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response **Outside Diameter:** 0.765 inches **Minimum Inside Bending Radius:** 5.750 inches **Connection Style:** Swivel nut flare 2nd end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 10500.0 pounds per square inch **Layer Composition And Location:** Outer layer braided corrosion resistant steel wire **Maximum Operating Pressure:**

maximum Operating Fressure.

3000.0 pounds per square inch

Thread Size:

0.750 inches 2nd end

Seat Angle: 37.0 degrees 2nd end

Hydrostatic Test Pressure:

6000.0 pounds per square inch

Flow Angle:

45.0 degrees 2nd end

Inside Surface Condition:

Smooth

Measuring Method And Length:

40.500 inches working

Thread Series Designator:

Unjf 1st end

Specification Data:

81343-as154 government standard

NSN 4720-01-168-7529

Nonmetallic Hose Assembly - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0