

View Online at <https://aerobasegroup.com/nsn/4720-01-168-9980>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

1.000 inches

Temperature Rating:

-40.0 degrees fahrenheit single response and 300.0 degrees fahrenheit single response

Outside Diameter:

1.500 inches

Minimum Inside Bending Radius:

6.000 inches

Exterior Color:

Blue

Hose Or Tubing Specification/std Data:

Sae j517, 100r4 size 16-81343 standard (includes industry or association standards, individual manufactureer standards, etc.).

Connection Style:

Swivel nut flare 2nd end

End Connection Design:

Straight 1st end

End Fitting Component And Material:

Complete fitting steel all ends

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

12 2nd end

Second End Relationship With First End:

Not identical

Burst Test Pressure:

1000.0 pounds per square inch

First End Swivel Action Capability:

Included

Layer Composition And Location:

1st layer braided textile yarn err-100

Maximum Operating Pressure:

250.0 pounds per square inch

Thread Size:

1.312 inches 2nd end

Seat Angle:

37.0 degrees 2nd end

Hydrostatic Test Pressure:

500.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Vacuum In Torr:

50.8

Inside Surface Condition:

Smooth

Measuring Method And Length:

13.375 inches

Second End Swivel Action Capability:

Not included

Special Features:

Inner conveying tube material-rubber, polyethylene

Thread Series Designator:

Un 2nd end

Specification Data:

Sae j517, 100r4 size 16-81343 national std/spec

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0