NSN 4720-01-169-1955

Nonmetallic Hose Assembly - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/4720-01-169-1955

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.219 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 160.0 degrees fahrenheit single response
Outside Diameter:
0.250 inches
Minimum Inside Bending Radius:
3.000 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
16000.0 pounds per square inch
Layer Composition And Location:
1st layer braided wire and 2nd layer braided wire and outer layer molded rubber, chloroprene
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
37.0 degrees 1st end
Outer Covering Environmental Protection:
Abrasion resistant and oil resistant and corrosion resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
15.375 inches working

Unjf 1st end

Specification Data:

Media For Which Designed:

Thread Series Designator:

96906-ms28759 government standard

Fuel/oil, hydrocarbon single response

NSN 4720-01-169-1955

Nonmetallic Hose Assembly - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0