NSN 4720-01-169-2509



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-01-169-2509 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.250 inches **Tempurature Rating:** -55.0 degrees fahrenheit and 300.0 degrees fahrenheit single response **Outside Diameter:** 0.580 inches **Minimum Inside Bending Radius:** 1.000 inches **Exterior Color:** Blue **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 2nd end **Connection Type:** Threaded internal tube 1st end **Features Provided:** Reusable end fittings **Burst Test Pressure:** 6000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided polyester cord and 2nd layer braided wire and outer layer molded rubber, chloroprene **Maximum Operating Pressure:** 1500.0 pounds per square inch **Thread Size:** 0.500 inches 2nd end Seat Angle: 45.0 degrees 2nd end **Hydrostatic Test Pressure:** 3000.0 pounds per square inch **Inside Surface Condition:** Smooth **Measuring Method And Length:**

Thread Series Designator:

Unf 2nd end

50.000 inches

NSN 4720-01-169-2509

Nonmetallic Hose Assembly - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0