## NSN 4720-01-169-3730

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-169-3730

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
1.375 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
1.750 inches
Minimum Inside Bending Radius:
10.500 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
12 1st end
Burst Test Pressure:
2000.0 pounds per square inch
Layer Composition And Location:
1st layer braided fiber and 2nd layer braided steel wire and outer layer molded rubber, synthetic
Maximum Operating Pressure:
500.0 pounds per square inch
Thread Size:
1.875 inches 1st end
Seat Angle:
37.0 degrees 1st end
Inside Surface Condition:
Smooth
Measuring Method And Length:
15.000 inches
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Un 1st end
Shelf Life:
N/a

## NSN 4720-01-169-3730

Nonmetallic Hose Assembly - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A542a0