## NSN 4720-01-169-3745

Air Duct Hose - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-01-169-3745

Round Wall Thickness: Between 0.020 inches and 0.060 inches Inside Diameter: 1.000 inches first end Minimum Inside Bending Radius: 1.000 inches Endlength: 1.000 inches first end Connection Style: Round first end Connection Type: Soft first end Features Provided: Abrasion resistant End Inside Diameter: 1.000 inches first end Maximum Operating Pressure: 12.0 pounds per square inch Measuring Method And Length: 10.250 inches External Operating Pressure: 6.0 pounds per square inch Special Features: Nomex fabric plies, nonmetallic helical wire reinforcement zytel 103 Material: Plastic polyamide 2nd ply Style Designator: Helically wound continous wire supported Shelf Life: N/a Unit Of Measure: Demilitarization: No Fitig:	Cross Sectional Shape:
Between 0.020 inches and 0.060 inches  Inside Diameter:  1.000 inches first end  Minimum Inside Bending Radius:  1.000 inches  Endlength:  1.000 inches first end  Connection Style: Round first end  Connection Type: Soft first end  Features Provided: Abrasion resistant  End Inside Diameter:  1.000 inches first end  Maximum Operating Pressure:  12.0 pounds per square inch  Measuring Method And Length:  10.250 inches  External Operating Pressure:  6.0 pounds per square inch  Special Features: Nomex fabric plies, nonmetallic helical wire reinforcement zytel 103  Material: Plastic polyamide 2nd ply  Style Designator: Helically wound continous wire supported  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No	Round
Inside Diameter:  1.000 inches first end Minimum Inside Bending Radius:  1.000 inches Endlength:  1.000 inches first end Connection Style: Round first end Connection Type: Soft first end Features Provided: Abrasion resistant End Inside Diameter:  1.000 inches first end Maximum Operating Pressure:  12.0 pounds per square inch Measuring Method And Length:  10.250 inches External Operating Pressure: 6.0 pounds per square inch Special Features: Nomex fabric plies, nonmetallic helical wire reinforcement zytel 103 Material: Plastic polyamide 2nd ply Style Designator: Helically wound continous wire supported Shelf Life: N/a Unit Of Measure: Demilitarization: No	Wall Thickness:
1.000 inches first end Minimum Inside Bending Radius: 1.000 inches Endlength: 1.000 inches first end Connection Style: Round first end Connection Type: Soft first end Features Provided: Abrasion resistant End Inside Diameter: 1.000 inches first end Maximum Operating Pressure: 12.0 pounds per square inch Measuring Method And Length: 10.250 inches External Operating Pressure: 6.0 pounds per square inch Special Features: Nomex fabric plies, nonmetallic helical wire reinforcement zytel 103 Material: Plastic polyamide 2nd ply Style Designator: Helically wound continous wire supported Shelf Life: N/a Unit Of Measure: Demilitarization: No	Between 0.020 inches and 0.060 inches
Minimum Inside Bending Radius:  1.000 inches Endlength:  1.000 inches first end Connection Style: Round first end Connection Type: Soft first end Features Provided: Abrasion resistant End Inside Diameter: 1.000 inches first end Maximum Operating Pressure: 12.0 pounds per square inch Measuring Method And Length: 10.250 inches External Operating Pressure: 6.0 pounds per square inch Special Features: Nomex fabric plies, nonmetallic helical wire reinforcement zytel 103 Material: Plastic polyamide 2nd ply Style Designator: Helically wound continous wire supported Shelf Life: N/a Unit Of Measure: Demilitarization: No	Inside Diameter:
Endlength:  1.000 inches first end Connection Style: Round first end Connection Type: Soft first end Features Provided: Abrasion resistant End Inside Diameter: 1.000 inches first end Maximum Operating Pressure: 12.0 pounds per square inch Measuring Method And Length: 10.250 inches External Operating Pressure: 6.0 pounds per square inch Special Features: Nomex fabric plies, nonmetallic helical wire reinforcement zytel 103 Material: Plastic polyamide 2nd ply Style Designator: Helically wound continous wire supported Shelf Life: N/a Unit Of Measure: Demilitarization: No	1.000 inches first end
Endlength:  1.000 inches first end  Connection Style: Round first end  Connection Type: Soft first end  Features Provided: Abrasion resistant  End Inside Diameter: 1.000 inches first end  Maximum Operating Pressure: 12.0 pounds per square inch  Measuring Method And Length: 10.250 inches  External Operating Pressure: 6.0 pounds per square inch  Special Features: Nomex fabric plies, nonmetallic helical wire reinforcement zytel 103  Material: Plastic polyamide 2nd ply  Style Designator: Helically wound continous wire supported  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No	Minimum Inside Bending Radius:
1.000 inches first end Connection Style: Round first end Connection Type: Soft first end Features Provided: Abrasion resistant End Inside Diameter: 1.000 inches first end Maximum Operating Pressure: 12.0 pounds per square inch Measuring Method And Length: 10.250 inches External Operating Pressure: 6.0 pounds per square inch Special Features: Nomex fabric plies, nonmetallic helical wire reinforcement zytel 103 Material: Plastic polyamide 2nd ply Style Designator: Helically wound continous wire supported Shelf Life: N/a Unit Of Measure: Demilitarization: No	1.000 inches
Connection Style: Round first end Connection Type: Soft first end Features Provided: Abrasion resistant End Inside Diameter: 1.000 inches first end Maximum Operating Pressure: 12.0 pounds per square inch Measuring Method And Length: 10.250 inches External Operating Pressure: 6.0 pounds per square inch Special Features: Nomex fabric plies, nonmetallic helical wire reinforcement zytel 103 Material: Plastic polyamide 2nd ply Style Designator: Helically wound continous wire supported Shelf Life: N/a Unit Of Measure: Demilitarization: No	Endlength:
Round first end Connection Type: Soft first end Features Provided: Abrasion resistant End Inside Diameter: 1.000 inches first end Maximum Operating Pressure: 12.0 pounds per square inch Measuring Method And Length: 10.250 inches External Operating Pressure: 6.0 pounds per square inch Special Features: Nomex fabric plies, nonmetallic helical wire reinforcement zytel 103 Material: Plastic polyamide 2nd ply Style Designator: Helically wound continous wire supported Shelf Life: N/a Unit Of Measure: Demilitarization: No	1.000 inches first end
Connection Type: Soft first end Features Provided: Abrasion resistant End Inside Diameter: 1.000 inches first end Maximum Operating Pressure: 12.0 pounds per square inch Measuring Method And Length: 10.250 inches External Operating Pressure: 6.0 pounds per square inch Special Features: Nomex fabric plies, nonmetallic helical wire reinforcement zytel 103 Material: Plastic polyamide 2nd ply Style Designator: Helically wound continous wire supported Shelf Life: N/a Unit Of Measure: Demilitarization: No	Connection Style:
Soft first end  Features Provided: Abrasion resistant  End Inside Diameter: 1.000 inches first end  Maximum Operating Pressure: 12.0 pounds per square inch  Measuring Method And Length: 10.250 inches  External Operating Pressure: 6.0 pounds per square inch  Special Features: Nomex fabric plies, nonmetallic helical wire reinforcement zytel 103  Material: Plastic polyamide 2nd ply  Style Designator: Helically wound continous wire supported  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No	Round first end
Features Provided: Abrasion resistant End Inside Diameter: 1.000 inches first end Maximum Operating Pressure: 12.0 pounds per square inch Measuring Method And Length: 10.250 inches External Operating Pressure: 6.0 pounds per square inch Special Features: Nomex fabric plies, nonmetallic helical wire reinforcement zytel 103 Material: Plastic polyamide 2nd ply Style Designator: Helically wound continous wire supported Shelf Life: N/a Unit Of Measure: Demilitarization: No	Connection Type:
Abrasion resistant  End Inside Diameter:  1.000 inches first end  Maximum Operating Pressure:  12.0 pounds per square inch  Measuring Method And Length:  10.250 inches  External Operating Pressure:  6.0 pounds per square inch  Special Features:  Nomex fabric plies, nonmetallic helical wire reinforcement zytel 103  Material:  Plastic polyamide 2nd ply  Style Designator:  Helically wound continous wire supported  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	Soft first end
End Inside Diameter:  1.000 inches first end  Maximum Operating Pressure:  12.0 pounds per square inch  Measuring Method And Length:  10.250 inches  External Operating Pressure:  6.0 pounds per square inch  Special Features:  Nomex fabric plies, nonmetallic helical wire reinforcement zytel 103  Material:  Plastic polyamide 2nd ply  Style Designator:  Helically wound continous wire supported  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	Features Provided:
1.000 inches first end  Maximum Operating Pressure:  12.0 pounds per square inch  Measuring Method And Length:  10.250 inches  External Operating Pressure:  6.0 pounds per square inch  Special Features:  Nomex fabric plies, nonmetallic helical wire reinforcement zytel 103  Material:  Plastic polyamide 2nd ply  Style Designator:  Helically wound continous wire supported  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	Abrasion resistant
Maximum Operating Pressure:  12.0 pounds per square inch  Measuring Method And Length:  10.250 inches  External Operating Pressure:  6.0 pounds per square inch  Special Features:  Nomex fabric plies, nonmetallic helical wire reinforcement zytel 103  Material:  Plastic polyamide 2nd ply  Style Designator:  Helically wound continous wire supported  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	End Inside Diameter:
12.0 pounds per square inch  Measuring Method And Length:  10.250 inches  External Operating Pressure: 6.0 pounds per square inch  Special Features: Nomex fabric plies, nonmetallic helical wire reinforcement zytel 103  Material: Plastic polyamide 2nd ply  Style Designator: Helically wound continous wire supported  Shelf Life: N/a  Unit Of Measure: Demilitarization: No	1.000 inches first end
Measuring Method And Length:  10.250 inches  External Operating Pressure: 6.0 pounds per square inch  Special Features: Nomex fabric plies, nonmetallic helical wire reinforcement zytel 103  Material: Plastic polyamide 2nd ply  Style Designator: Helically wound continous wire supported  Shelf Life: N/a  Unit Of Measure: Demilitarization: No	Maximum Operating Pressure:
External Operating Pressure: 6.0 pounds per square inch Special Features: Nomex fabric plies, nonmetallic helical wire reinforcement zytel 103 Material: Plastic polyamide 2nd ply Style Designator: Helically wound continous wire supported Shelf Life: N/a Unit Of Measure: Demilitarization: No	12.0 pounds per square inch
External Operating Pressure:  6.0 pounds per square inch  Special Features:  Nomex fabric plies, nonmetallic helical wire reinforcement zytel 103  Material:  Plastic polyamide 2nd ply  Style Designator:  Helically wound continous wire supported  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	Measuring Method And Length:
6.0 pounds per square inch  Special Features:  Nomex fabric plies, nonmetallic helical wire reinforcement zytel 103  Material:  Plastic polyamide 2nd ply  Style Designator:  Helically wound continous wire supported  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	10.250 inches
Special Features:  Nomex fabric plies, nonmetallic helical wire reinforcement zytel 103  Material:  Plastic polyamide 2nd ply  Style Designator:  Helically wound continous wire supported  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	External Operating Pressure:
Nomex fabric plies, nonmetallic helical wire reinforcement zytel 103  Material:  Plastic polyamide 2nd ply  Style Designator:  Helically wound continous wire supported  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	6.0 pounds per square inch
Material: Plastic polyamide 2nd ply Style Designator: Helically wound continous wire supported Shelf Life: N/a Unit Of Measure: Demilitarization: No	Special Features:
Plastic polyamide 2nd ply  Style Designator: Helically wound continous wire supported  Shelf Life: N/a Unit Of Measure: Demilitarization: No	Nomex fabric plies, nonmetallic helical wire reinforcement zytel 103
Style Designator: Helically wound continous wire supported Shelf Life: N/a Unit Of Measure: Demilitarization: No	Material:
Helically wound continous wire supported  Shelf Life: N/a Unit Of Measure: Demilitarization: No	Plastic polyamide 2nd ply
Shelf Life: N/a Unit Of Measure: Demilitarization: No	Style Designator:
N/a Unit Of Measure: Demilitarization: No	Helically wound continous wire supported
Unit Of Measure: Demilitarization: No	Shelf Life:
Demilitarization:	N/a
No	Unit Of Measure:
No	
	Demilitarization:
Fiig:	No
	Fiig:
A229a0	A229a0