NSN 4720-01-169-4899

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-169-4899

| Cross Sectional Shape: | | | | |
|---|--|--|--|--|
| Round | | | | |
| Thread Class: | | | | |
| 3b 1st end | | | | |
| Thread Direction: | | | | |
| Right-hand 1st end | | | | |
| Inside Diameter: | | | | |
| 0.410 inches | | | | |
| Tempurature Rating: | | | | |
| -65.0 degrees fahrenheit and 450.0 degrees fahrenheit single response | | | | |
| Outside Diameter: | | | | |
| 0.560 inches | | | | |
| Minimum Inside Bending Radius: | | | | |
| 4.620 inches | | | | |
| Exterior Color: | | | | |
| Black | | | | |
| Connection Style: | | | | |
| Swivel nut, flareless 1st end | | | | |
| End Connection Design: | | | | |
| Straight 1st end | | | | |
| Connection Type: | | | | |
| Threaded internal tube 1st end | | | | |
| Features Provided: | | | | |
| Reusable end fittings | | | | |
| Burst Test Pressure: | | | | |
| 8000.0 pounds per square inch | | | | |
| Layer Composition And Location: | | | | |
| Outer layer braided corrosion resistant steel wire | | | | |
| Maximum Operating Pressure: | | | | |
| 1500.0 pounds per square inch | | | | |
| Thread Size: | | | | |
| 0.750 inches 1st end | | | | |
| Seat Angle: | | | | |
| 12.0 degrees 1st end | | | | |
| Hydrostatic Test Pressure: | | | | |
| 3000.0 pounds per square inch | | | | |
| Inside Surface Condition: | | | | |
| Smooth | | | | |
| Measuring Method And Length: | | | | |
| 11.125 inches | | | | |
| Sunnlamentary Features: | | | | |

The current approved sources (rnvc 2) have indicated their part numbers contained asbestos. They continue to manufacture the same part number without asbestos material

NSN 4720-01-169-4899

Nonmetallic Hose Assembly - Page 2 of 2



| _ | | • | _ | |
|---|-------|---------|------|-----------|
| ı | hread | Series | 1)66 | ignator: |
| • | mcaa | OCI ICS | 000 | igilatoi. |

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0