

View Online at <https://aerobasegroup.com/nsn/4720-01-170-0786>

Cross Sectional Shape:

Round

Inside Diameter:

1.000 inches

Temperature Rating:

-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

Flange Thickness:

0.425 inches 2nd end

Outside Diameter:

1.520 inches

Minimum Inside Bending Radius:

14.000 inches

Exterior Color:

Black

Angle Between Rigid Elbow Fittings In Deg:

250.0

Flange Outside Diameter:

2.125 inches 2nd end

Connection Style:

Plain w/ gasket groove (sae flanged head) 2nd end

End Flange Construction:

Solid 2nd end

End Connection Design:

Elbow 2nd end

Connection Type:

Plain face flange 2nd end

Burst Test Pressure:

20000.0 pounds per square inch

Layer Composition And Location:

1st layer spirally laid steel wire and 2nd layer spirally laid steel wire and 3rd layer spirally laid steel wire and 4th layer spirally laid steel wire and outer layer molded rubber, synthetic

Maximum Operating Pressure:

5000.0 pounds per square inch

Hydrostatic Test Pressure:

1000.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Inside Surface Condition:

Smooth

Measuring Method And Length:

40.500 inches

Flange Style:

Round w/ out bolt holes 2nd end

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0