NSN 4720-01-170-7055

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-170-7055

Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.250 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Outside Diameter:
0.498 inches
Minimum Inside Bending Radius:
2.750 inches
Exterior Color:
Black
Connection Style:
Swivel, plain 2nd end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded external pipe 2nd end
Features Provided:
Perforated outer cover
Burst Test Pressure:
12000.0 pounds per square inch
Layer Composition And Location:
1st layer braided fiber and 2nd layer braided fiber and outer layer molded polyurethane
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.250 inches 2nd end
Hydrostatic Test Pressure:
6000.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
42.000 inches
Thread Series Designator:
Npt 1st end
Shelf Life:
N/a
Unit Of Measure:

--

NSN 4720-01-170-7055

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0