NSN 4720-01-170-7055

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-170-7055

| Cross Sectional Shape: |
|---|
| Round |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.250 inches |
| Tempurature Rating: |
| -65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.498 inches |
| Minimum Inside Bending Radius: |
| 2.750 inches |
| Exterior Color: |
| Black |
| Connection Style: |
| Swivel, plain 2nd end |
| End Connection Design: |
| Straight 2nd end |
| Connection Type: |
| Threaded external pipe 2nd end |
| Features Provided: |
| Perforated outer cover |
| Burst Test Pressure: |
| 12000.0 pounds per square inch |
| Layer Composition And Location: |
| 1st layer braided fiber and 2nd layer braided fiber and outer layer molded polyurethane |
| Maximum Operating Pressure: |
| 3000.0 pounds per square inch |
| Thread Size: |
| 0.250 inches 2nd end |
| Hydrostatic Test Pressure: |
| 6000.0 pounds per square inch |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 42.000 inches |
| Thread Series Designator: |
| Npt 1st end |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 4720-01-170-7055

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0