Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-170-7062

Cr	oss Sectional Shape:
Ro	bund
Th	read Class:
3b	1st end
Th	read Direction:
Ri	ght-hand 1st end
Ins	side Diameter:
0.4	106 inches
Те	mpurature Rating:
-65	5.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Οι	utside Diameter:
0.5	585 inches
Mi	nimum Inside Bending Radius:
4.6	520 inches
Co	onnection Style:
Sw	vivel nut, flareless 2nd end
En	nd Connection Design:
Str	raight 1st end
Co	onnection Type:
Th	readed internal tube 1st end
Fe	atures Provided:
Re	eusable end fittings
Bu	ırst Test Pressure:
80	00.0 pounds per square inch
La	yer Composition And Location:
Οι	ater layer braided corrosion resistant steel wire
Ма	aximum Operating Pressure:
15	00.0 pounds per square inch
Th	read Size:
0.7	750 inches 2nd end
Se	at Angle:
12	.0 degrees 2nd end
Hy	drostatic Test Pressure:
30	00.0 pounds per square inch
Flo	ow Angle:
90	.0 degrees 2nd end
Va	icuum In Torr:
28	.0
Ins	side Surface Condition:
Sn	nooth
Me	easuring Method And Length:
20	.500 inches

AeroBase Group

Thread Series Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A542a0