## NSN 4720-01-171-1961

**Cross Sectional Shape:** 

Round

Thread Class: 3b 1st end

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-171-1961

Thread Direction:
Right-hand 1st end
Inside Diameter:
0.375 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 265.0 degrees fahrenheit single response
Outside Diameter:
0.570 inches
Minimum Inside Bending Radius:
2.000 inches
Exterior Color:
Natural
End Application:
43999; environmental control system coolant line
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability and reusable end fittings
Burst Test Pressure:
475.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
190.0 pounds per square inch
Thread Size:
0.562 inches 2nd end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
285.0 pounds per square inch
Flow Angle:
130.0 degrees 2nd end
Outer Covering Environmental Protection:
Abrasion resistant and corrosion resistant

## NSN 4720-01-171-1961

Nonmetallic Hose Assembly - Page 2 of 2



Inside Surface Condition:
Smooth
Measuring Method And Length:
16.500 inches working
Thread Series Designator:
Unf 2nd end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A542a0