Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-171-4202

•	
	tional Shape:
Round	
Thread Dir	
Right-hand	
Inside Dia	
0.250 inche	
Tempuratu	ure Rating:
-40.0 degre	ees fahrenheit and 200.0 degrees fahrenheit single response
Outside D	iameter:
0.500 inche	es
Minimum	Inside Bending Radius:
3.000 inche	es
Connectio	n Style:
Swivel, pla	ain 2nd end
End Conn	ection Design:
Straight 2n	d end
Connectio	n Type:
Threaded i	nternal pipe 1st end
Burst Test	Pressure:
1500.0 pou	unds per square inch
Layer Con	nposition And Location:
1st layer br	raided synthetic cord and outer layer molded rubber, chloroprene
Maximum	Operating Pressure:
375.0 pour	nds per square inch
Thread Siz	ze:
0.125 inche	es 2nd end
Outer Cov	ering Environmental Protection:
Abrasion re	esistant and oil resistant and ozone resistant
Inside Sur	face Condition:
Smooth	
Measuring	Method And Length:
13.322 incl	nes
Special Fe	atures:
Threaded e	external end fitted w/90 degree elbow w/0.125 inch threaded plug
Thread Se	ries Designator:
Npt 1st end	t
Shelf Life:	
N/a	
Unit Of Me	easure:
Demilitariz	zation:
No	

NSN 4720-01-171-4202

Nonmetallic Hose Assembly - Page 2 of 2

Fiig: A542a0

