## NSN 4720-01-171-4419

**Cross Sectional Shape:** 

Round

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-171-4419

Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.998 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response
Outside Diameter:
1.300 inches
Minimum Inside Bending Radius:
3.000 inches
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
12 2nd end
Burst Test Pressure:
3000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1250.0 pounds per square inch
Thread Size:
1.312 inches 2nd end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
2500.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Inside Surface Condition:
Convoluted
Measuring Method And Length:
18.000 inches working
Thread Series Designator:
Un 2nd end

## NSN 4720-01-171-4419

Nonmetallic Hose Assembly - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0