Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-171-6655

C	Cross Sectional Shape:
F	Round
T	Thread Class:
3	3b 1st end
T	Thread Direction:
F	Right-hand 1st end
h	nside Diameter:
С	0.406 inches
T	Tempurature Rating:
-	65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
C	Dutside Diameter:
С	0.562 inches
N	Ainimum Inside Bending Radius:
4	I.625 inches
C	Connection Style:
S	Swivel nut, flareless 1st end
E	End Connection Design:
S	Straight 1st end
C	Connection Type:
T	Threaded internal tube 1st end
F	Features Provided:
F	Reusable end fittings
E	Burst Test Pressure:
8	3000.0 pounds per square inch
L	ayer Composition And Location:
C	Duter layer braided corrosion resistant steel wire
N	Maximum Operating Pressure:
1	500.0 pounds per square inch
T	Thread Size:
С	0.750 inches 1st end
S	Seat Angle:
1	2.0 degrees 1st end
ŀ	lydrostatic Test Pressure:
3	3000.0 pounds per square inch
۷	/acuum In Torr:
5	50.8
h	nside Surface Condition:
S	Smooth
N	Measuring Method And Length:
2	28.000 inches working
T	Thread Series Designator:
	Jnjf 1st end

NSN 4720-01-171-6655

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

