Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-171-6656

Cross Se	ectional Shape:
Round	
Thread C	lass:
3b 1st en	d
Thread D	virection:
Right-han	nd 1st end
Inside Di	ameter:
0.406 incl	hes
Tempura	ture Rating:
-65.0 deg	rees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside I	Diameter:
0.562 incl	hes
Minimum	Inside Bending Radius:
4.620 incl	hes
Connecti	ion Style:
Swivel nu	t, flareless 1st end
End Con	nection Design:
Straight 1	st end
Connecti	on Type:
Threaded	Internal tube 1st end
Features	Provided:
Reusable	end fittings
Burst Te	st Pressure:
8000.0 pc	ounds per square inch
Layer Co	mposition And Location:
Outer lay	er braided corrosion resistant steel wire
Maximun	n Operating Pressure:
-	ounds per square inch
Thread S	ize:
0.750 incl	hes 1st end
Seat Ang	
-	rees 1st end
-	tic Test Pressure:
-	bunds per square inch
Vacuum	In Torr:
50.8	
	Irface Condition:
Smooth	
	ng Method And Length:
	ches working
	eries Designator:
Unjf 1st e	nd

NSN 4720-01-171-6656

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

