NSN 4720-01-171-7140

Unf 1st end

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-171-7140

| Cross Sectional Shape: |
|--|
| Round |
| Thread Class: |
| 3b 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.375 inches |
| Tempurature Rating: |
| -65.0 degrees fahrenheit and 300.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.555 inches |
| Minimum Inside Bending Radius: |
| 0.870 inches |
| Exterior Color: |
| Green |
| Connection Style: |
| Swivel nut flare 1st end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded internal tube 1st end |
| Features Provided: |
| Internal support |
| Burst Test Pressure: |
| 500.0 pounds per square inch |
| Layer Composition And Location: |
| 1st layer braided corrosion resistant steel wire and outer layer rubber impregnated fabric |
| Maximum Operating Pressure: |
| 125.0 pounds per square inch |
| Thread Size: |
| 0.562 inches 1st end |
| Seat Angle: |
| 37.0 degrees 1st end |
| Hydrostatic Test Pressure: |
| 250.0 pounds per square inch |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 17.000 inches working |
| Thread Series Designator: |

NSN 4720-01-171-7140

Nonmetallic Hose Assembly - Page 2 of 2



| _ | | | | | |
|----|---|---|----|----|----|
| ٠. | n | _ | I+ | 18 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0