## NSN 4720-01-172-2499

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-172-2499

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.500 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.880 inches
Minimum Inside Bending Radius:
2.000 inches
Exterior Color:
Black
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Burst Test Pressure:
900.0 pounds per square inch
Layer Composition And Location:
1st layer braided textile yarn and 2nd layer braided textile yarn and outer layer molded rubber, synthetic
Maximum Operating Pressure:
225.0 pounds per square inch
Thread Size:
0.750 inches 1st end
Seat Angle:
45.0 degrees 1st end
Hydrostatic Test Pressure:
450.0 pounds per square inch
Vacuum In Torr:
50.8
Inside Surface Condition:
Smooth
Measuring Method And Length:

58.000 inches

## NSN 4720-01-172-2499

Nonmetallic Hose Assembly - Page 2 of 2



Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Unf 1st end
Specification Or Standard:
8 size
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A542a0