## NSN 4720-01-172-7558

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-172-7558

Cross Sectional Shape:

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.250 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.625 inches
Minimum Inside Bending Radius:
4.000 inches
Exterior Color:
Black
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
11000.0 pounds per square inch
Layer Composition And Location:
1st layer braided wire and outer layer molded rubber, synthetic
Maximum Operating Pressure:
3250.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
6500.0 pounds per square inch
Outer Covering Environmental Protection:
Weatherproof
Inside Surface Condition:
Smooth
Measuring Method And Length:
216.000 inches

.. .. \_ .....

Media For Which Designed:

Hydraulic fluid single response

## NSN 4720-01-172-7558

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designator:
Unf 1st end
Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0