NSN 4720-01-173-5196

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-173-5196 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.406 inches **Tempurature Rating:** -58.0 degrees fahrenheit and 302.0 degrees fahrenheit single response **Outside Diameter:** 0.770 inches **Minimum Inside Bending Radius:** 1.750 inches **Connection Style:** Swivel nut, inverted flare 2nd end **End Connection Design:** Straight 2nd end **Connection Type:** Threaded internal tube 1st end Thready Qty Per Inch (tpi): 18 2nd end **Burst Test Pressure:** 2000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided textile yarn and 2nd layer braided corrosion resistant steel wire and outer layer braided polyester cord **Maximum Operating Pressure:** 500.0 pounds per square inch **Thread Size:** 0.750 inches 2nd end Seat Angle: 45.0 degrees 2nd end **Hydrostatic Test Pressure:** 1000.0 pounds per square inch **Inside Surface Condition:** Smooth

Measuring Method And Length:

56.000 inches

Media For Which Designed:

Air single response

Thread Series Designator:

Uns 2nd end

NSN 4720-01-173-5196

Nonmetallic Hose Assembly - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0