NSN 4720-01-174-1206

Cross Sectional Shape:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-174-1206

Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.500 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Outside Diameter:
0.875 inches
Minimum Inside Bending Radius:
3.500 inches
Exterior Color:
Black
End Application:
Truck tractor, model c0-1950-b i.H.C.
Connection Style:
Plain 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded external pipe 1st end
Burst Test Pressure:
900.0 pounds per square inch
Layer Composition And Location:
1st layer braided rayon cord and 2nd layer braided rayon cord and outer layer molded rubber, synthetic
Maximum Operating Pressure:
225.0 pounds per square inch
Thread Size:
0.375 inches 1st end
Hydrostatic Test Pressure:
450.0 pounds per square inch
Outer Covering Environmental Protection:
Ozone resistant and oil resistant and weatherproof
Inside Surface Condition:
Smooth
Measuring Method And Length:
20.000 inches working
Media For Which Designed:
Air single response
Thread Series Designator:
Npt 1st end

NSN 4720-01-174-1206

Nonmetallic Hose Assembly - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0