## NSN 4720-01-175-2924

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-175-2924
Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.625 inches
Tempurature Rating:
-100.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside Diameter:
0.905 inches
Minimum Inside Bending Radius:
6.500 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
End Fitting Component And Material:
Complete fitting stainless steel all ends
Connection Type:
Threaded internal tube 1st end
Second End Relationship With First End:
Identical
Burst Test Pressure:
20000.0 pounds per square inch
First End Swivel Action Capability:
Not included
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire err-100
Maximum Operating Pressure:
4000.0 pounds per square inch
Thread Size:
0.875 inches 1st end

Seat Angle:

37.0 degrees 1st end

**Outer Covering Environmental Protection:** 

Hydraulic solution resistant

**Inside Surface Condition:** 

Smooth

**Measuring Method And Length:** 

26.000 inches

## NSN 4720-01-175-2924

Nonmetallic Hose Assembly - Page 2 of 2



Special Features:
Inner conveying tube material-plastic, polytetrafluoroethylene
Thread Series Designator:
Unf 1st end
Shelf Life:
N/a

Demilitarization:

**Unit Of Measure:** 

No

Fiig:

A542a0