

View Online at <https://aerobasegroup.com/nsn/4720-01-176-2814>

Cross Sectional Shape:

Round

Thread Class:

3a 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.375 inches

Temperature Rating:

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Outside Diameter:

0.625 inches

Minimum Inside Bending Radius:

4.000 inches

Exterior Color:

Black

Connection Style:

Inverted flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded external tube 1st end

Burst Test Pressure:

2600.0 pounds per square inch

Layer Composition And Location:

1st layer braided rayon cord and 2nd layer braided rayon cord and outer layer molded rubber, neoprene

Maximum Operating Pressure:

650.0 pounds per square inch

Thread Size:

0.562 inches 1st end

Seat Angle:

12.0 degrees 1st end

Hydrostatic Test Pressure:

1300.0 pounds per square inch

Outer Covering Environmental Protection:

Abrasion resistant and heat resistant and oil resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

600.000 inches

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0