NSN 4720-01-176-5963

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-176-5963

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.750 inches
Tempurature Rating:
-40.0 degrees fahrenheit single response and 250.0 degrees fahrenheit single response
Outside Diameter:
1.250 inches
Minimum Inside Bending Radius:
9.500 inches
Exterior Color:
Black
Hose Or Tubing Specification/std Data:
Sae j517, 100r2, type at-81343 standard (includes industry or association standards, individual manufactureer standards, etc.).
End Connection Design:
Straight 1st end
End Fitting Component And Material:
Complete fitting steel all ends
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Thready Qty Per Inch (tpi):
12 1st end
Second End Relationship With First End:
Identical
Burst Test Pressure:
9000.0 pounds per square inch
First End Swivel Action Capability:
Not included
Layer Composition And Location:
1st layer braided steel wire err-100
Maximum Operating Pressure:
2250.0 pounds per square inch
Thread Size:
1.062 inches 1st end

37.0 degrees 1st end

Seat Angle:

NSN 4720-01-176-5963

No Fiig: A542a0

Nonmetallic Hose Assembly - Page 2 of 2



Hydrostatic Test Pressure:
4500.0 pounds per square inch
Outer Covering Environmental Protection:
Abrasion resistant and oil resistant and weatherproof
Inside Surface Condition:
Smooth
Measuring Method And Length:
77.000 inches
Special Features:
Inner conveying tube material-rubber, synthetic
Media For Which Designed:
Fuel/oil, hydrocarbon single response and hydraulic fluid, silicate-ester base single response and hydraulic fluid, water base single
response
Thread Series Designator:
Un 1st end
Specification Data:
Sae j517, 100r2, type at-81343 national std/spec
Shelf Life:
N/a
Unit Of Measure:

Demilitarization: