Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-176-7100

View Online at https://aerobasegroup.com/nsn/4720-01-176-7100
Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.212 inches
Tempurature Rating:
-67.0 degrees fahrenheit and 400.0 degrees fahrenheit single response
Outside Diameter:
0.390 inches
Minimum Inside Bending Radius:
1.500 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
12000.0 pounds per square inch
Layer Composition And Location:
1st layer braided corrosion resistant steel wire and outer layer molded rubber, synthetic
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.437 inches 1st end
Seat Angle:
12.0 degrees 1st end
Outer Covering Environmental Protection:
Water resistant and heat resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
20.000 inches working
Special Features:
C/o thin wall polytetrafluoroethylene inner tube and hi-pac outer braid consisting of densely packed small diameter stainless steel wires braid
in a uniform pattern
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Unjf 1st end

## NSN 4720-01-176-7100

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0

