## NSN 4720-01-176-9516

Nonmetallic Hose - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-01-176-9516

| Ones On the state of the state |
|---|
| Cross Sectional Shape:  |
| Round   |
| Inside Diameter:  |
| 0.380 inches  |
| Tempurature Rating:   |
| -40.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response   |
| Outside Diameter:   |
| 0.680 inches  |
| Minimum Inside Bending Radius:  |
| 3.500 inches  |
| Burst Test Pressure:  |
| 16000.0 pounds per square inch single response  |
| Layer Composition And Location:   |
| 1st layer braided wire err-100  |
| Maximum Operating Pressure:   |
| 4000.0 pounds per square inch single response   |
| Hydrostatic Test Pressure:  |
| 8000.0 pounds per square inch single response   |
| Outer Covering Environmental Protection:  |
| Oil resistant and weatherproof  |
| Inside Surface Condition:   |
| Smooth  |
| Material:   |
| Rubber synthetic tube   |
| Media For Which Designed:   |
| Hydraulic fluid, water base single response   |
| Specification Data:   |
| 81343-sae j517, 100r2 professional/industrial association standard  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A541z0  |
|   |
|   |