NSN 4720-01-177-3714

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-177-3714 **Cross Sectional Shape:** Round **Inside Diameter:** 1.000 inches **Exterior Color:** Gray, light **Quick Disconnect Size:** 1.000 inches 2nd end **Connection Style:** Cam or lever (external) 2nd end **End Connection Design:** Straight 2nd end **Connection Type:** Internal quick disconnect 1st end **Burst Test Pressure:** 400.0 pounds per square inch **Layer Composition And Location:** 2nd layer braided fabric or 1st layer braided fabric or outer layer molded rubber, natural or 2nd layer spirally wrapped fabric or 1st layer spirally wrapped fabric or 2nd layer woven fabric or 1st layer woven fabric or outer layer molded rubber, synthetic **Maximum Operating Pressure:** 150.0 pounds per square inch **Hydrostatic Test Pressure:** 300.0 pounds per square inch **Outer Covering Environmental Protection:** Ozone resistant and weatherproof **Inside Surface Condition:** Smooth **Measuring Method And Length:** 240.000 inches **Special Features:** Banding clamps for hose fittings cres per a-a-52506 **Special Markings:** Mark each section of hose with a blue longitudinal stripe, denoting for potabl (drinking) water only; per fed- std-595, color number 25102 Media For Which Designed: Water single response **Specification Or Standard:** 2 class and 3 grade Shelf Life: N/a

No

Unit Of Measure:

Demilitarization:

NSN 4720-01-177-3714

Nonmetallic Hose Assembly - Page 2 of 2



Fiig:

A542a0