Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-177-3922

#### **Cross Sectional Shape:**

Round

**Thread Class:** 

3b 1st end

# **Thread Direction:**

Right-hand 1st end

## Inside Diameter:

1.250 inches

#### **Tempurature Rating:**

-40.0 degrees fahrenheit single response and 300.0 degrees fahrenheit single response

#### **Outside Diameter:**

1.800 inches

Minimum Inside Bending Radius:

#### 8.000 inches

Exterior Color:

Blue

#### Hose Or Tubing Specification/std Data:

Sae j517, 100r4-81343 standard (includes industry or association standards, individual manufactureer standards, etc.).

## **Connection Style:**

Swivel nut flare 1st end

## End Connection Design:

Straight 1st end

#### End Fitting Component And Material:

Complete fitting steel all ends

#### **Connection Type:**

Threaded internal tube 1st end

#### **Features Provided:**

Reusable end fittings

Thready Qty Per Inch (tpi):

12 1st end

#### Second End Relationship With First End:

Identical

# **Burst Test Pressure:**

800.0 pounds per square inch

# First End Swivel Action Capability:

Not included

# Layer Composition And Location:

1st layer braided textile yarn err-100

# Maximum Operating Pressure:

200.0 pounds per square inch

# Thread Size:

1.625 inches 1st end

# NSN 4720-01-177-3922

Nonmetallic Hose Assembly - Page 2 of 2



Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 400.0 pounds per square inch **Outer Covering Environmental Protection:** Oil resistant Vacuum In Torr: 50.0 Inside Surface Condition: Smooth Measuring Method And Length: 84.000 inches **Thread Series Designator:** Un 1st end **Specification Data:** Sae j517, 100r4-81343 national std/spec Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A542a0