Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-177-4708

Cross Sec	ctional Shape:
Round	
Thread Di	rection:
Right-hand	d 1st end
Inside Dia	
0.188 inch	es
Tempurat	ure Rating:
-	ees fahrenheit and 200.0 degrees fahrenheit single response
Outside D	
0.500 inch	es
Minimum	Inside Bending Radius:
3.500 inch	
Connectio	on Style:
Plain 1st e	
End Conn	ection Design:
Straight 1s	
Connectio	on Type:
Threaded	external pipe 1st end
Burst Tes	t Pressure:
12000.0 p	ounds per square inch
Layer Cor	nposition And Location:
1st layer b	raided corrosion resistant steel wire and outer layer molded rubber, synthetic
Maximum	Operating Pressure:
3000.0 po	unds per square inch
Thread Si	ze:
0.125 inch	es 1st end
Outer Cov	vering Environmental Protection:
Oil resista	nt and weatherproof
Inside Su	rface Condition:
Smooth	
Measuring	g Method And Length:
36.000 inc	hes
Media For	Which Designed:
Fuel/oil, h	ydrocarbon single response
Thread Se	eries Designator:
Nptf 1st er	nd
Shelf Life	:
N/a	
Unit Of Me	easure:
Demilitari	zation:
No	

NSN 4720-01-177-4708

Nonmetallic Hose Assembly - Page 2 of 2

Fiig: A542a0

