NSN 4720-01-178-8471

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-178-8471

Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
2.000 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
2.560 inches
Minimum Inside Bending Radius:
12.000 inches
Connection Style:
Swivel, plain 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded external pipe 2nd end
Burst Test Pressure:
400.0 pounds per square inch
Layer Composition And Location:
1st layer braided textile yarn and 1st layer woven cotton with interwoven steel wire and 2nd layer braided textile yarn and outer layer
molded rubber, synthetic
Maximum Operating Pressure:
100.0 pounds per square inch
Thread Size:
2.000 inches 1st end
Hydrostatic Test Pressure:
200.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Outer Covering Environmental Protection:
Oil resistant and ozone resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
26.000 inches
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Npsh 2nd end

N/a

Shelf Life:

NSN 4720-01-178-8471

Nonmetallic Hose Assembly - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A542a0