

View Online at <https://aerobasegroup.com/nsn/4720-01-178-8471>

Cross Sectional Shape:

Round

Thread Direction:

Right-hand 1st end

Inside Diameter:

2.000 inches

Temperature Rating:

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Outside Diameter:

2.560 inches

Minimum Inside Bending Radius:

12.000 inches

Connection Style:

Swivel, plain 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Threaded external pipe 2nd end

Burst Test Pressure:

400.0 pounds per square inch

Layer Composition And Location:

1st layer braided textile yarn and 1st layer woven cotton with interwoven steel wire and 2nd layer braided textile yarn and outer layer molded rubber, synthetic

Maximum Operating Pressure:

100.0 pounds per square inch

Thread Size:

2.000 inches 1st end

Hydrostatic Test Pressure:

200.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Outer Covering Environmental Protection:

Oil resistant and ozone resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

26.000 inches

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Npsh 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0