Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-179-1324

# **Cross Sectional Shape:**

Round

**Thread Class:** 

2b 1st end

# **Thread Direction:**

Right-hand 1st end

# **Inside Diameter:**

0.260 inches

#### **Tempurature Rating:**

-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response

### **Outside Diameter:**

0.570 inches

Minimum Inside Bending Radius:

#### 3.000 inches

**Exterior Color:** 

Blue

#### **Connection Style:**

Swivel nut flare 1st end

#### **End Connection Design:**

Straight 1st end

# Connection Type:

Threaded internal tube 1st end

### **Burst Test Pressure:**

20000.0 pounds per square inch

# Layer Composition And Location:

1st layer braided corrosion resistant steel wire and outer layer molded rubber, ethylene propylene

# Maximum Operating Pressure:

5000.0 pounds per square inch

#### **Thread Size:**

0.438 inches 1st end

#### Seat Angle:

37.0 degrees 1st end

# Hydrostatic Test Pressure:

10000.0 pounds per square inch

# Inside Surface Condition:

Smooth

# Measuring Method And Length:

36.000 inches

# Thread Series Designator:

Unf 1st end

#### Shelf Life:

N/a

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0