

View Online at <https://aerobasegroup.com/nsn/4720-01-179-7611>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.620 inches

Temperature Rating:

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Outside Diameter:

0.930 inches

Minimum Inside Bending Radius:

6.000 inches

Angle Between Rigid Elbow Fittings In Deg:

45.0

Connection Style:

Swivel nut flare 2nd end

End Connection Design:

Elbow 2nd end

Connection Type:

Threaded internal tube 1st end

Burst Test Pressure:

11000.0 pounds per square inch

Layer Composition And Location:

1st layer braided wire and outer layer molded rubber, synthetic

Maximum Operating Pressure:

2750.0 pounds per square inch

Thread Size:

0.875 inches 2nd end

Seat Angle:

37.0 degrees and 45.0 degrees 2nd end

Hydrostatic Test Pressure:

5500.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Inside Surface Condition:

Smooth

Measuring Method And Length:

43.370 inches

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0