## NSN 4720-01-179-9870

**Cross Sectional Shape:** 

Round

Smooth

Thread Class: 3a 1st end

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-179-9870

Thread Direction:
Right-hand 1st end
Inside Diameter:
0.375 inches
Tempurature Rating:
-40.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response
Outside Diameter:
0.840 inches
Minimum Inside Bending Radius:
5.000 inches
Connection Style:
External seat for gasket seal (boss) 1st end
End Connection Design:
Straight 1st end
End Fitting Component And Material:
Complete fitting nickel alloy all ends
Connection Type:
Threaded external boss 1st end
Features Provided:
Reusable end fittings
Thready Qty Per Inch (tpi):
12 1st end
Second End Relationship With First End:
Identical
Burst Test Pressure:
18000.0 pounds per square inch
First End Swivel Action Capability:
Not included
Layer Composition And Location:
1st layer spiral interlocked corrosion resistant steel err-100
Maximum Operating Pressure:
4500.0 pounds per square inch
Thread Size:
1.188 inches 1st end
Hydrostatic Test Pressure:
9000.0 pounds per square inch
Inside Surface Condition:

## NSN 4720-01-179-9870

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length:
86.750 inches
Special Features:
Inner conveying tube material-rubber, synthetic
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Un 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A542a0