Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-179-9870

Cross Sectional Shape:
Round
Thread Class:
3a 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.375 inches
Tempurature Rating:
-40.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response
Outside Diameter:
0.840 inches
Minimum Inside Bending Radius:
5.000 inches
Connection Style:
External seat for gasket seal (boss) 1st end
End Connection Design:
Straight 1st end
End Fitting Component And Material:
Complete fitting nickel alloy all ends
Connection Type:
Threaded external boss 1st end
Features Provided:
Reusable end fittings
Thready Qty Per Inch (tpi):
Second End Relationship With First End:
Identical
Burst Test Pressure:
18000.0 pounds per square inch
First End Swivel Action Capability:
Not included
Layer Composition And Location:
1st layer spiral interlocked corrosion resistant steel err-100
Maximum Operating Pressure:
4500.0 pounds per square inch Thread Size:
1.188 inches 1st end
Hydrostatic Test Pressure:
9000.0 pounds per square inch
Inside Surface Condition:
Smooth

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length: 86.750 inches **Special Features:** Inner conveying tube material-rubber, synthetic Media For Which Designed: Fuel/oil, hydrocarbon single response **Thread Series Designator:** Un 1st end Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A542a0