Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-180-8662

Cross Sectional Shape:
Round
Thread Class:
3b 2nd end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.250 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.600 inches
Minimum Inside Bending Radius:
4.000 inches
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 2nd end
Burst Test Pressure:
20000.0 pounds per square inch
Layer Composition And Location:
1st layer braided wire and outer layer molded rubber, synthetic
Maximum Operating Pressure:
5000.0 pounds per square inch
Thread Size:
0.437 inches 2nd end
Seat Angle:
37.0 degrees and 45.0 degrees 2nd end
Hydrostatic Test Pressure:
10000.0 pounds per square inch
Flow Angle:
45.0 degrees 2nd end
Inside Surface Condition:
Smooth
Measuring Method And Length:
29.500 inches
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Unf 2nd end

NSN 4720-01-180-8662

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0

