

View Online at <https://aerobasegroup.com/nsn/4720-01-181-0107>

**Cross Sectional Shape:**

Round

**Thread Class:**

2b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.500 inches

**Temperature Rating:**

-40.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response

**Outside Diameter:**

0.875 inches

**Minimum Inside Bending Radius:**

7.000 inches

**Hose Or Tubing Specification/std Data:**

Sae j517, 100r2, type at-81343 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Connection Style:**

Swivel nut flare 1st end

**End Connection Design:**

Straight 1st end

**End Fitting Component And Material:**

Complete fitting steel all ends

**Fitting Component And Surface Treatment:**

Complete fitting cadmium 1st end

**Connection Type:**

Threaded internal tube 1st end

**Features Provided:**

Electrostatic discharge capability and nonskive

**Second End Relationship With First End:**

Identical

**Burst Test Pressure:**

14000.0 pounds per square inch

**First End Swivel Action Capability:**

Not included

**Layer Composition And Location:**

1st layer braided steel wire err-100

**Maximum Operating Pressure:**

3500.0 pounds per square inch

**Thread Size:**

0.750 inches 1st end

**Seat Angle:**

37.0 degrees 1st end

**Hydrostatic Test Pressure:**

7000.0 pounds per square inch

**Outer Covering Environmental Protection:**

Oil resistant and waterproof

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

364.000 inches working

**Special Features:**

Inner conveying tube material-rubber, synthetic

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Thread Series Designator:**

Unf 1st end

**Specification Data:**

Sae j517, 100r2, type at-81343 national std/spec

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0