NSN 4720-01-183-2320

Cross Sectional Shape:

Round

Thread Class: 3b 1st end

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-183-2320

Thread Direction:			
Right-hand 1st end			
Inside Diameter:			
0.298 inches			
Tempurature Rating:			
-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response			
Outside Diameter:			
Between 0.535 inches and 0.595 inches			
Minimum Inside Bending Radius:			
5.000 inches			
Connection Style:			
Swivel nut, inverted flare 2nd end			
End Connection Design:			
Straight 1st end			
Connection Type:			
Threaded internal tube 1st end			
Thready Qty Per Inch (tpi):			
20 2nd end			
Burst Test Pressure:			
14000.0 pounds per square inch			
Layer Composition And Location:			
Outer layer braided corrosion resistant steel wire			
Maximum Operating Pressure:			
3000.0 pounds per square inch			
Thread Size:			
0.719 inches 2nd end			
Seat Angle:			
8.5 degrees 2nd end			
Hydrostatic Test Pressure:			
6000.0 pounds per square inch			
Flow Angle:			
42.0 degrees 2nd end			
Inside Surface Condition:			
Smooth			
Measuring Method And Length:			
15.880 inches working			
Special Features:			
42 degrees elbow has a 1.000 in. Leg length			

NSN 4720-01-183-2320

Nonmetallic Hose Assembly - Page 2 of 2



		_
Thread	l Series	Designator:

Unjs 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0