## NSN 4720-01-184-6989

N/a

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-184-6989

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.610 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 300.0 degrees fahrenheit single response  Outside Diameter:
0.880 inches
Minimum Inside Bending Radius:
1.500 inches
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
1000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
250.0 pounds per square inch
Thread Size:
1.062 inches 1st end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
500.0 pounds per square inch
Flow Angle:
45.0 degrees 1st end
Inside Surface Condition:
Convoluted
Measuring Method And Length:
17.750 inches working
Thread Series Designator:
Unf 2nd end
Shelf Life:

## NSN 4720-01-184-6989

Nonmetallic Hose Assembly - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A542a0