Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-185-9469

	nape:
Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Tempurature Ratir	ıg:
-40.0 degrees fahre	nheit and 149.0 degrees fahrenheit single response
Outside Diameter:	
0.250 inches	
Minimum Inside B	ending Radius:
2.000 inches	
Connection Style:	
Swivel nut flare 2nd	end
End Connection D	esign:
Straight 1st end	
Connection Type:	
Threaded internal to	ibe 1st end
Burst Test Pressu	re:
3000.0 pounds per	square inch
Layer Compositio	n And Location:
Outer layer braided	corrosion resistant steel wire
Maximum Operati	ng Pressure:
1000.0 pounds per	square inch
Thread Size:	
0.438 inches 1st en	d
Seat Angle:	
37.0 degrees 2nd e	nd
Flow Angle:	
45.0 degrees 2nd e	nd
Inside Surface Co	
Smooth	
Measuring Method	And Length:
6.500 inches worki	
Supplementary Fe	
	reviewed for asbestos material. The current approved sources (rnvc 2) have indicated their part numbers containe
	tinue to manufacture the same part number without asbestos material
Thread Series Des	
Unjf 1st end	-g
Shelf Life:	
N/a	
Unit Of Measure:	

## NSN 4720-01-185-9469

Nonmetallic Hose Assembly - Page 2 of 2

Demilitarization:

No

Fiig:

A542a0

