Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-186-4422

Cross Sectional Sh	ape:
Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.344 inches	
Tempurature Rating	
	heit and 300.0 degrees fahrenheit single response
Outside Diameter:	
0.547 inches	
Minimum Inside Be	nding Radius:
2.500 inches	
Connection Style:	
Swivel nut flare 1st e	nd
End Connection De	sign:
Straight 1st end	
Connection Type:	
Threaded internal tub	be 1st end
Features Provided:	
Reusable end fittings	
Burst Test Pressure	2:
6000.0 pounds per s	quare inch
Layer Composition	And Location:
1st layer braided cor	rosion resistant steel wire, partial coverage and outer layer braided corrosion resistant steel wire
Maximum Operating	g Pressure:
100.0 pounds per sq	uare inch
Thread Size:	
0.562 inches 1st end	
Seat Angle:	
33.0 degrees 1st end	I
Hydrostatic Test Pr	essure:
3000.0 pounds per s	quare inch
Inside Surface Con	dition:
Smooth	
Measuring Method	And Length:
8.875 inches workin	-
Media For Which De	-
Fuel/oil, hydrocarbo	-
Thread Series Desig	
Unjf 1st end	,

Nonmetallic Hose Assembly - Page 2 of 2



**Specification Data:** 

96906-ms87029 government standard

Shelf Life:

N/a

Unit Of Measure:

---

## Demilitarization:

Yes - demil/mli

Fiig:

A542a0