Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-187-1153

Cross Se	ectional Shape:
Round	
Thread C	lass:
3b 1st en	d
Thread D	irection:
Right-har	d 1st end
Inside Di	ameter:
0.438 inc	nes
Tempura	ture Rating:
-40.0 deg	rees fahrenheit and 300.0 degrees fahrenheit single response
Outside	Diameter:
0.641 inc	nes
Minimum	Inside Bending Radius:
3.500 incl	hes
Connecti	on Style:
Swivel nu	t flare 2nd end
End Con	nection Design:
Straight 1	st end
Connecti	on Type:
Threaded	internal tube 1st end
Thready	Qty Per Inch (tpi):
12 1st en	d
Burst Te	st Pressure:
5000.0 pc	ounds per square inch
Layer Co	mposition And Location:
1st layer	braided corrosion resistant steel wire, partial coverage and outer layer braided corrosion resistant steel wire
Maximun	n Operating Pressure:
1000.0 pc	ounds per square inch
Thread S	ize:
1.062 inc	hes 1st end
Seat Ang	le:
37.0 degr	ees 2nd end
Hydrosta	tic Test Pressure:
2500.0 pc	ounds per square inch
Flow Ang	yle:
45.0 degr	ees 2nd end
Inside Sı	Irface Condition:
Smooth	
Measurir	ng Method And Length:
12.500 in	ches working
Media Fo	r Which Designed:
Fuel/oil	hydrocarbon single response

Nonmetallic Hose Assembly - Page 2 of 2



**Thread Series Designator:** 

Unj 1st end

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0