NSN 4720-01-187-6910

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-187-6910

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.844 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 300.0 degrees fahrenheit single response
Outside Diameter:
1.175 inches
Minimum Inside Bending Radius:
5.500 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
12 2nd end
Burst Test Pressure:
3000.0 pounds per square inch
Layer Composition And Location:
1st layer braided corrosion resistant steel wire, partial coverage and outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
750.0 pounds per square inch
Thread Size:
1.312 inches 2nd end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
1500.0 pounds per square inch
Outer Covering Environmental Protection:
Alcohol resistant and solvent resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
10.125 inches working
Media For Which Designed:

Fuel/oil, hydrocarbon single response

NSN 4720-01-187-6910

Nonmetallic Hose Assembly - Page 2 of 2



Inread Series Designator:
Uns 1st end
Specification Or Standard
16 size
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A542a0