Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-188-3581

Round         Thread Class:         3b 1st end         Thread Direction:         Right-hand 1st end         Inside Diameter:         0.250 inches         Temparture Rating:         65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response         Outside Diameter:         0.460 inches         Minimun Inside Bending Radius:         1.250 inches         Connection Style:         Swivel nut flare 1st end         End Connection Design:         Straight 1st end         Connection Type:         Threaded internal tube 1st end         Burst Test Pressure:         4000.0 pounds per square inch         Layer Composition And Location:         Outer layer braided corrosion resistant steel wire         Maximu Operating Pressure:         100.0 pounds per square inch         Exert Size:         0.438 inches 1st end         Straight Test Pressure:         100.0 pounds per square inch         Herd Size:         1.2.0 degrees 1st end         Sizet Angle:         2.7.0 degrees 1st end         Hydrostatic Test Pressure:         200.0 pounds per square inch         Inside Surface Co	Cros	ss Sectional Shape:
Baist and         Thread Direction:         Right-hand 1st end         Inside Diameter:         0.250 inches         Tempurature Rating:         -65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response         Outside Diameter:         0.460 inches         Minimum Inside Bending Radius:         1.250 inches         Connection Style:         Swivel nut flare 1st end         End Connection Design:         Straight 1st end         Connection Type:         Thread dinternal tube 1st end Burst Test Pressure:         4000.0 pounds per square inch         Layer Composition And Location:         Outer layer braided corrosion resistant steel wire         Maximum Operating Pressure:         100.0.0 pounds per square inch         Thread Size:         0.438 inches 1st end         Sext Angle:         37.0 degrees 1st end         Hydrostatic Test Pressure:         2000.0 pounds per square inch         Inside Surface Condition:         Smooth         Measuring Method And Length:         4.750 inches         Thread Series Designator:         Unjf 1st end         Sheff Life: </th <th></th> <th></th>		
Thread Direction: Right-hand 1st end Inside Diameter: 0.250 inches Tempurature Rating: -65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response Outside Diameter: 0.460 inches Minimum Inside Bending Radius: 1.250 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 4000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 100.0.0 pounds per square inch Thread Size: 0.438 inches 1st end Set Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 2000.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 4.750 inches Thread Series Designator: Unjf 1st end Sheff Life:	Thre	ead Class:
Right-hand 1st end Inside Diameter: 0.250 inches Tempurature Rating: -65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response Outside Diameter: 0.460 inches Minimum Inside Bending Radius: 1.250 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 4000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1000.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 2000.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 4.750 inches Thread Series Designator: Unjf 1st end Sheff Life:	3b 1	st end
Inside Diameter: 0.250 inches  Iempurature Rating: -65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response Outside Diameter: 0.460 inches  Minimum Inside Bending Radius: 1.250 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 4000.0 pounds per square inch Layer Composition And Location: 0.0100 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 2000.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 4.750 inches Charles Thread Series Designator: Unjf 1st end Charles Thread Series Designator: Charles Charl	Thre	ead Direction:
Inside Diameter: 0.250 inches  Iempurature Rating: -65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response Outside Diameter: 0.460 inches  Minimum Inside Bending Radius: 1.250 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 4000.0 pounds per square inch Layer Composition And Location: 0.0100 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 2000.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 4.750 inches Charles Thread Size: Unjf 1st end Charles Char	Righ	nt-hand 1st end
Tempurature Rating: -65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response Outside Diameter: 0.460 inches Minimum Inside Bending Radius: 1.250 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 4000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1000.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 2000.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 4.750 inches Thread Sizes Designator: Unif 1st end Sheff Life:	Insid	de Diameter:
-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single responseOutside Diameter:0.460 inchesMinimum Inside Bending Radius:1.250 inchesConnection Style:Swivel nut flare 1st endEnd Connection Design:Straight 1st endConnection Type:Threaded internal tube 1st endBurst Test Pressure:4000.0 pounds per square inchLayer Composition And Location:Outer layer braided corrosion resistant steel wireMaximum Operating Pressure:1000.0 pounds per square inchThread Size:0.438 inches 1st endSeat Angle:37.0 degrees 1st endHydrostatic Test Pressure:2000.0 pounds per square inchInside Surface Condition:SmoothMeasuring Method And Length:4.750 inchesThread Series Designator:Unjf 1st endSheff Life:	0.25	0 inches
Outside Diameter:         0.460 inches         Minimum Inside Bending Radius:         1.250 inches         Connection Style:         Swivel nut flare 1st end         End Connection Design:         Straight 1st end         Connection Type:         Threaded internal tube 1st end         Burst Test Pressure:         4000.0 pounds per square inch         Layer Composition And Location:         Outer layer braided corrosion resistant steel wire         Maximum Operating Pressure:         1000.0 pounds per square inch         Thread Size:         0.438 inches 1st end         Seat Angle:         37.0 degrees 1st end         Hydrostatic Test Pressure:         2000.0 pounds per square inch         Inside Surface Condition:         Smooth         Measuring Method And Length:         4.750 inches         Thread Series Designator:         Unjf 1st end         Sheff Life:	Tem	npurature Rating:
0.460 inches Minimun Inside Bending Radius: 1.250 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 4000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1000.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 2000.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 4.750 inches Thread Series Designator: Unjf 1st end Sheff Life:	-65.0	0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response
Minimum Inside Bending Radius: 1.250 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 4000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1000.0 pounds per square inch Thread Size: 0.438 inches 1st end Set Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 2000.0 pounds per square inch Hydrostatic Test Pressure: 2000.0 pounds per square inch Thread Size: 0.438 inches 1st end Set Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 2000.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 4.750 inches Thread Series Designator: Unjf 1st end Shelf Life:	Outs	side Diameter:
1.250 inches         Connection Style:         Swivel nut flare 1st end         End Connection Design:         Straight 1st end         Connection Type:         Threaded internal tube 1st end         Burst Test Pressure:         4000.0 pounds per square inch         Layer Composition And Location:         Outer layer braided corrosion resistant steel wire         Maximum Operating Pressure:         1000.0 pounds per square inch         Thread Size:         0.438 inches 1st end         Seat Angle:         37.0 degrees 1st end         Hydrostatic Test Pressure:         2000.0 pounds per square inch         Inside Surface Condition:         Smooth         Measuring Method And Length:         4.750 inches         Thread Series Designator:         Unjf 1st end         Sheff Life:	0.46	0 inches
Connection Style:Swivel nut flare 1st endEnd Connection Design:Straight 1st endConnection Type:Threaded internal tube 1st endBurst Test Pressure:4000.0 pounds per square inchLayer Composition And Location:Outer layer braided corrosion resistant steel wireMaximum Operating Pressure:1000.0 pounds per square inchThread Size:0.438 inches 1st endSeat Angle:37.0 degrees 1st endHydrostatic Test Pressure:2000.0 pounds per square inchInside Surface Condition:SmoothMeasuring Method And Length:4.750 inchesThread Series Designator:Unjf 1st endShelf Life:	Mini	imum Inside Bending Radius:
Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 4000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1000.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 2000.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 4.750 inches Thread Series Designator: Unjf 1st end Shelf Life:	1.25	0 inches
End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 4000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1000.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 2000.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 4.750 inches Thread Series Designator: Unjf 1st end Shelf Life:	Con	nection Style:
Straight 1st endConnection Type:Threaded internal tube 1st endBurst Test Pressure:4000.0 pounds per square inchLayer Composition And Location:Outer layer braided corrosion resistant steel wireMaximum Operating Pressure:1000.0 pounds per square inchThread Size:0.438 inches 1st endSeat Angle:37.0 degrees 1st endHydrostatic Test Pressure:2000.0 pounds per square inchHiside Surface Condition:SmoothMeasuring Method And Length:4.750 inchesThread Series Designator:Unjf 1st endShelf Life:	Swiv	vel nut flare 1st end
Connection Type: Threaded internal tube 1st end Burst Test Pressure: 4000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1000.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 2000.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 4.750 inches Thread Series Designator: Unjf 1st end Shelf Life:	End	Connection Design:
Threaded internal tube 1st end Burst Test Pressure: 4000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1000.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 2000.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 4.750 inches Thread Series Designator: Unjf 1st end Shelf Life:	Strai	ight 1st end
Burst Test Pressure: 4000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1000.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 2000.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 4.750 inches Thread Series Designator: Unjf 1st end Shelf Life:	Con	nection Type:
4000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1000.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 2000.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 4.750 inches Thread Series Designator: Unjf 1st end Shelf Life:	Thre	eaded internal tube 1st end
Layer Composition And Location:Outer layer braided corrosion resistant steel wireMaximum Operating Pressure:1000.0 pounds per square inchThread Size:0.438 inches 1st endSeat Angle:37.0 degrees 1st endHydrostatic Test Pressure:2000.0 pounds per square inchInside Surface Condition:SmoothMeasuring Method And Length:4.750 inchesUnjf 1st endShelf Life:	Burs	st Test Pressure:
Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1000.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 2000.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 4.750 inches Thread Series Designator: Unjf 1st end Shelf Life:	4000	0.0 pounds per square inch
Maximum Operating Pressure: 1000.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 2000.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 4.750 inches Thread Series Designator: Unjf 1st end Shelf Life:	Laye	er Composition And Location:
1000.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 2000.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 4.750 inches Thread Series Designator: Unjf 1st end Shelf Life:	Oute	er layer braided corrosion resistant steel wire
Thread Size: 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 2000.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 4.750 inches Thread Series Designator: Unjf 1st end Shelf Life:	Max	imum Operating Pressure:
0.438 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 2000.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 4.750 inches Thread Series Designator: Unjf 1st end Shelf Life:	1000	0.0 pounds per square inch
Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 2000.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 4.750 inches Thread Series Designator: Unjf 1st end Shelf Life:	Thre	ead Size:
37.0 degrees 1st end Hydrostatic Test Pressure: 2000.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 4.750 inches Thread Series Designator: Unjf 1st end Shelf Life:	0.43	8 inches 1st end
Hydrostatic Test Pressure: 2000.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 4.750 inches Thread Series Designator: Unjf 1st end Shelf Life:	Seat	t Angle:
2000.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 4.750 inches Thread Series Designator: Unjf 1st end Shelf Life:	37.0	degrees 1st end
Inside Surface Condition: Smooth Measuring Method And Length: 4.750 inches Thread Series Designator: Unjf 1st end Shelf Life:	Hyd	rostatic Test Pressure:
Smooth Measuring Method And Length: 4.750 inches Thread Series Designator: Unjf 1st end Shelf Life:	2000	0.0 pounds per square inch
Measuring Method And Length: 4.750 inches Thread Series Designator: Unjf 1st end Shelf Life:	Insid	de Surface Condition:
4.750 inches Thread Series Designator: Unjf 1st end Shelf Life:	Smo	poth
Thread Series Designator: Unjf 1st end Shelf Life:	Меа	suring Method And Length:
Unjf 1st end Shelf Life:	4.75	0 inches
Shelf Life:	Thre	ead Series Designator:
	Unjf	1st end
N/a	She	If Life:
	N/a	

---

Nonmetallic Hose Assembly - Page 2 of 2

Demilitarization:

No

Fiig:

A542a0

