## NSN 4720-01-189-6585

**Cross Sectional Shape:** 

Round

Smooth

Thread Class: 3b 1st end

Thread Direction: Right-hand 1st end Inside Diameter: 0.602 inches

**Tempurature Rating:** 

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-189-6585

-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response
Outside Diameter:
Between 0.950 inches and 0.990 inches
Minimum Inside Bending Radius:
4.000 inches
Angle Between Rigid Elbow Fittings In Deg:
90.0
Connection Style:
Swivel nut, flareless 1st end
End Connection Design:
Elbow 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Burst Test Pressure:
12000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
1.062 inches 1st end
Seat Angle:
12.0 degrees 1st end
Hydrostatic Test Pressure:
6000.0 pounds per square inch
Flow Angle:
90.0 degrees 1st end
Outer Covering Environmental Protection:
Fuel resistant and solvent resistant and vibration resistant and heat resistant
Inside Surface Condition:

## NSN 4720-01-189-6585

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length:
14.500 inches working
Thread Series Designator:
Unjf 1st end
Specification Data:
81343-as120 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A542a0