Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-189-6587

| Cross Sectional Shape: |
|---|
| Round |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.375 inches |
| Tempurature Rating: |
| -40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.620 inches |
| Minimum Inside Bending Radius: |
| 3.000 inches |
| Connection Style: |
| Swivel, plain 1st end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded external pipe 1st end |
| Burst Test Pressure: |
| 1600.0 pounds per square inch |
| Layer Composition And Location: |
| 1st layer braided textile yarn and outer layer molded rubber, synthetic |
| Maximum Operating Pressure: |
| 400.0 pounds per square inch |
| Thread Size: |
| 0.250 inches 1st end |
| Outer Covering Environmental Protection: |
| Oil resistant and ozone resistant |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 33.000 inches |
| Media For Which Designed: |
| Air and hydraulic fluid single response |
| Thread Series Designator: |
| Npt 1st end |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| |

NSN 4720-01-189-6587

Nonmetallic Hose Assembly - Page 2 of 2

Fiig: A542a0

