## NSN 4720-01-189-8587

**Cross Sectional Shape:** 

Round

Thread Class: 3b 1st end

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-189-8587

The ADV setting
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.625 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside Diameter:
0.789 inches
Minimum Inside Bending Radius:
6.500 inches
Angle Between Rigid Elbow Fittings In Deg:
150.0
Connection Style:
Swivel nut, flareless 1st end
End Connection Design:
Elbow 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Thready Qty Per Inch (tpi):
12 1st end
Burst Test Pressure:
5000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1000.0 pounds per square inch
Thread Size:
1.062 inches 1st end
Seat Angle:
12.0 degrees 1st end
Hydrostatic Test Pressure:
2000.0 pounds per square inch
Flow Angle:
90.0 degrees 1st end
Outer Covering Environmental Protection:
Acid resistant and fuel resistant and oil resistant and oxidation resistant

## NSN 4720-01-189-8587

Nonmetallic Hose Assembly - Page 2 of 2



Inside Surface Condition:
Smooth
<b>Measuring Method And Length:</b>
28.500 inches working
Thread Series Designator:
Un 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

**Fiig:** A542a0