NSN 4720-01-189-8602

Nonmetallic Hose Assembly - Page 1 of 2



| uruu | • |
|---|---|
| View Online at https://aerobasegroup.com/nsn/4720-01-189-8602 | |
| Cross Sectional Shape: | |
| Round | |
| Thread Class: | |
| 3b 1st end | |
| Thread Direction: | |
| Right-hand 1st end | |
| Inside Diameter: | |
| 0.298 inches | |
| Tempurature Rating: | |
| -67.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response | |
| Outside Diameter: | |
| 0.475 inches | |
| Minimum Inside Bending Radius: | |
| 2.500 inches | |
| Connection Style: | |
| Swivel nut flare 2nd end | |
| End Connection Design: | |
| Straight 1st end | |
| Connection Type: | |
| Threaded internal tube 1st end | |
| Features Provided: | |
| Electrostatic discharge capability | |
| Burst Test Pressure: | |
| 10500.0 pounds per square inch | |
| Layer Composition And Location: | |
| Outer layer braided corrosion resistant steel wire | |
| Maximum Operating Pressure: | |
| 3000.0 pounds per square inch | |
| Thread Size: | |
| 0.562 inches 2nd end | |
| Seat Angle: | |
| 37.0 degrees 2nd end | |
| Hydrostatic Test Pressure: | |
| 6000.0 pounds per square inch | |

Flow Angle:

90.0 degrees 2nd end

Outer Covering Environmental Protection:

Fuel resistant and heat resistant and oil resistant and solvent resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

23.875 inches

NSN 4720-01-189-8602

Nonmetallic Hose Assembly - Page 2 of 2



| | •• | | • | _ | | |
|---|-----|----|------|--------|------|--------|
| ı | hre | ลด | Seri | 26 I I | PSIU | nator: |
| • | | uu | CCII | | COIG | mator. |

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0