NSN 4720-01-190-1014

Cross Sectional Shape:

Round

Thread Class: 3b 1st end

Thread Direction:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-190-1014

| Right-hand 1st end | | | | |
|---|--|--|--|--|
| Inside Diameter: | | | | |
| 0.765 inches | | | | |
| Tempurature Rating: | | | | |
| -65.0 degrees fahrenheit single response and 300.0 degrees fahrenheit single response | | | | |
| Outside Diameter: | | | | |
| 1.120 inches | | | | |
| Minimum Inside Bending Radius: | | | | |
| 2.000 inches | | | | |
| Connection Style: | | | | |
| Swivel nut flare 1st end | | | | |
| End Connection Design: | | | | |
| Straight 1st end | | | | |
| Connection Type: | | | | |
| Threaded internal tube 1st end | | | | |
| Thready Qty Per Inch (tpi): | | | | |
| 12 1st end | | | | |
| Burst Test Pressure: | | | | |
| 1200.0 pounds per square inch | | | | |
| Layer Composition And Location: | | | | |
| Outer layer braided corrosion resistant steel wire | | | | |
| Maximum Operating Pressure: | | | | |
| 300.0 pounds per square inch | | | | |
| Thread Size: | | | | |
| 1.062 inches 1st end | | | | |
| Seat Angle: | | | | |
| 37.0 degrees 1st end | | | | |
| Hydrostatic Test Pressure: | | | | |
| 600.0 pounds per square inch | | | | |
| Outer Covering Environmental Protection: | | | | |
| Oil resistant | | | | |
| Inside Surface Condition: | | | | |
| Convoluted | | | | |
| Measuring Method And Length: | | | | |
| 10.000 inches | | | | |
| Thread Series Designator: | | | | |
| Unj 1st end | | | | |

NSN 4720-01-190-1014

Nonmetallic Hose Assembly - Page 2 of 2



| _ | | | | |
|---|----|------|---|------|
| c | hο | JIF. | | ife: |
| J | | | _ | HG. |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0